

LOUDSPEAKERS - SUB BASS

NEXO ID110 SUB BASS



Features:

- Frequency Range 43 Hz – 130 Hz (+/- 3dB)
- Peak SPL 125dB (1m)
- Ultra-low profile allows flexible placement
- Versatile accessories available for mounting or rigging with eyebolts
- Can be used in Omni or Cardio modes

ID110 subs is ideal companions for ID speakers, enabling the configuration of compact, powerful, full range systems. 1x10" feature the same low profile – just 285mm high – allowing them to be positioned discreetly in walls, staircases or under furniture, ensuring low visual impact in prestigious installations. Ceiling/wall mounting plates and rigging eyebolts are available. Single (ID110) long-excursion 10" drivers are housed in Finnish birch plywood cabinets with a black structured paint finish. The ID110 features Speakon NL4 connectors. In addition to 4xM6 inserts, the cabinet also features an M20 base plate for use in pole-mounted mobile systems, and also side handles for easy portability. In use with NEXO NXAMP or DTD controllers, ID subwoofers can be deployed in traditional omnidirectional mode or in cardioid mode (using 2 x subwoofers and 2 x amplification channels). ID110 subs share the same phase response as other NEXO speakers, making them extremely easy to integrate in ID Series systems or systems using other NEXO modules. The ID110 Sub is also available in White.



Orbital Sound Ltd, 57 Acre Lane,
Brixton, London, SW2 5TN,
United Kingdom,
Tel: +44 207 501 6868
hire@orbitalsound.com
www.orbitalsound.com