

LOUDSPEAKERS


d&b audiotechnik E0 LOUDSPEAKER





The E0, d&b's smallest loudspeaker, produces superlative sound and tremendous output for small, near field, delay and surround sound situations, and with the addition of a subwoofer it can be used for music playback. With a frequency response that covers the 80 Hz to 20 kHz band and a 100° conical dispersion, the E0 will display identical directivity whether deployed horizontally or vertically. Incorporated into the cleverly shaped black or white polyamide cabinet is a self-locking ball joint with integrated mounting arm, magnetic shielding of the LF driver and either a quad push or two NL4 connectors.

Amplifiers

The E0 can be driven either by d&b's D6 or D12 dual channel power amplifiers configured for the E0. More detailed information on specific loudspeaker setups with d&b amplifiers is available either in the relevant loudspeaker or amplifier manuals.





E0 cabinet dimensions in mm (inch)

Features:

- Even Frequency Response Across the Ranges
- Easy to Set Up
- Very Reliable
- High Output To Size & Weight Ratio
- Flexible Range
- Integrated System Design
- Multi Functional Rigging
- Precise Pattern Control Applications:

- Theatre
- Conference
- Cinema
- Theme Parks
- Houses of Worship
- Leisure Facilities
- Voice Evacuation



Orbital Sound Ltd, 57 Acre Lane,
Brixton, London, SW2 5TN,
United Kingdom,
Tel: +44 207 501 6868
hire@orbitalsound.com
www.orbitalsound.com