LOUDSPEAKERS


d&b audiotechnik E0 LOUDSPEAKER





The E0, d&bs smallest loudspeaker, produces superlative sound and tremendous output for small, near field, delay and surround sound situations, and with the addition of a subwoofer it can be used for music playback. With a frequency response that covers the 80 Hz to 20 kHz band and a 100 conical dispersion, the E0 will display identical directivity whether deployed horizontally or vertically. Incorporated into the cleverly shaped black or white polyamide cabinet is a self-locking ball joint with integrated mounting arm, magnetic shielding of the LF driver and either a quad push or two NL4 connectors.

Amplifiers

The E0 can be driven either by d&bs D6 or D12 dual channel power amplifiers configured for the E0. More detailed information on specific loudspeaker setups with d&b amplifiers is available either in the relevant loudspeaker or amplifier manuals.







E0 cabinet dimensions in mm (inch)

Features:
• Even Frequency Response Across the Ranges
• Easy to Set Up
• Very Reliable
• High Output To Size & Weight Ratio
• Flexible Range
• Integrated System Design
• Multi Functional Rigging
• Precise Pattern Control Applications:
• Theatre
• Conference
• Cinema
• Theme Parks
• Houses of Worship
• Leisure Facilities
• Voice Evacuation

Orbital Sound Ltd, 57 Acre Lane,
Brixton, London, SW2 5TN,
United Kingdom,
Tel: +44 207 501 6868
hire@orbitalsound.com
www.orbitalsound.com