

LOUDSPEAKERS - SPM

GENELEC 8030A COMPACT BI-AMPED REFERENCE MONITOR



The very compact 8030A is a powerful bi-amplified nearfield monitor system ideal for project and home studios, workstations, installations, and surround sound monitoring. The MDE (Minimum Diffraction Enclosure) enclosure has rounded edges and a gently curved front and sides to achieve a very smooth frequency response and superb imaging qualities with minimized cabinet edge diffraction. Like all Genelec 8000 Series monitors, the 8030A also features the advanced Genelec Directivity Control Waveguide (DCW), a revolutionary flow-optimized reflex port design, optimized die-cast aluminium structure

with extremely durable semi-matt finish and acoustically optimized metal grilles. Low distortion drivers are driven by dedicated amplifiers after sophisticated filtering. Magnetic shielding, overload protection circuitry and versatile room response controls are standard. The versatile mounting features include integrated rear support points for wall and floor stands plus a further 3/8 inch thread for mounting on the cabinet base. Every Genelec 8030A monitor comes with an Iso-Pod (Isolation Positioner/Decoupler) as standard. The Iso-Pod is a clever mounting stand, which allows the system to perform in either the vertical or horizontal position. It also enables the acoustic axis of the monitor to be aimed at the listener, while acoustically and mechanically decoupling the monitor from the surface it is resting on.



Features:

- 19mm metal dome tweeter
- 130mm woofer
- Magnetic shielding
- Can mount on a 3/8th mic stand

Applications:

- Theatre
- Conference
- Cinema
- Rock n Roll
- Live Event
- Theme Parks
- Houses of Worship
- Leisure Facilities



Orbital Sound Ltd, 57 Acre Lane,
Brixton, London, SW2 5TN,
United Kingdom,
Tel: +44 207 501 6868
hire@orbitalsound.com
www.orbitalsound.com