LOUDSPEAKERS - SPM

GENELEC 1029A COMPACT BI-AMPED REFERENCE MONITOR



Applications:
- Theatre
- Conference
- Cinema
- Rock n Roll
- Live Event
- Theme Parks
- Houses of Worship
- Leisure Facilities

Features:
- 19mm metal dome tweeter
- 130mm woofer
- Magnetic shielding
- Can mount on a 3/8th mic stand

The extremely compact 1029A is a powerful bi-amplified nearfield monitor system ideal for project and home studios, digital workstations, and surround sound monitoring. The monitor has a very rugged cast aluminium construction and magnetic stray field shielding as default for every single unit. Vented speaker enclosure contains an amplification unit, including an active electronic crossover, overload protection circuitry and two power amplifiers, one for each driver. Genelecs unique Directivity Control Waveguide (DCW) is used to provide excellent stereo imaging and frequency balance, even in difficult acoustic environments. Versatile room response controls allow matching of the system to its surroundings. The 1029A is very easy to set up and use, the only connections required are the mains supply and the line level input. The input is made via balanced XLR female or 1/4 inch jack socket connector which can also be used in parallel.

Orbital Sound Ltd, 57 Acre Lane,
Brixton, London, SW2 5TN,
United Kingdom,
Tel: +44 207 501 6868
hire@orbitalsound.com
www.orbitalsound.com